

# ECOSTARTER

*Single-component water-based acrylic primer for wooden floors*



## Description

ECOSTARTER is a single-component water-based acrylic primer specific for water-based lacquering of wooden floors. ECOSTARTER has excellent chemical and physical properties has: transparency, easy sandability and adequate solid residue.

## Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	roller 8 mm / brush / spray
Thinning (if necessary)	DILUENTE DR H2O
Coverage	70-100 g/m <sup>2</sup>
Dust dry	20' <sup>(1)</sup>
Fingerprint dry	30' <sup>(1)</sup>
Sanding	12 h <sup>(1)</sup>
Overcoating without sanding	1-3 h <sup>(1)</sup>
Wood oxidation	low
Pore filling	good
Storage stability	1 year <sup>(2)</sup>
Packaging	5 L - 25 L
Tool cleaning	DILUENTE DNH 40 (with fresh product)

- 1 at 20°C and 65% R.H.
- 2 in original sealed containers at temperatures between +10°C and +25°C

## How to use

Shake well before use. ECOSTARTER has to be applied on wooden floors that have been filled, sanded and carefully vacuumed. It is possible after 2 hours from the first application (without sanding) or after 12/24 hours (prior sanding with 280/320 paper grit) to apply another coat of ECOSTARTER. The subsequent lacquering, previous proper sanding, has to be done with ECOSTAR, ECOSTAR 2K or ECOWOOD 2K (see technical data sheets).

**Notes:** if lacquering tannin wood species, it is suggested to run a preliminary test.

## Label elements

· Causes serious eye irritation.

· If medical advice is needed, have product container or label at hand. · Keep out of reach of children. · Wash thoroughly with water after use. · Wear protective gloves / protective clothing / eye protection / face protection. · IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. · If eye irritation persists: Get medical advice / attention.



## Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



[http://www.chimiver.com/tds/EN\\_ECOSTARTER.pdf](http://www.chimiver.com/tds/EN_ECOSTARTER.pdf)